

Page 1/11

Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2015 Reviewed on 10/10/2015

1 Identification

- · Product identifier
- · Trade name: UT18AEV
- · Application of the substance / the mixture Metal working
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Carpenter Technology Corp PO Box 14662, Reading, PA 19612 110 West Bern Street

READING, PA 19601

USA

- · Information department: Health and Safety Department
- · Emergency telephone number: During normal opening times: +1 (610) 208-2134

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 1A H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

arsenic

lead

nickel

· Hazard statements

May cause an allergic skin reaction.

May cause cancer.

(Contd. on page 2)

Printing date 10/19/2015 Reviewed on 10/10/2015

Trade name: UT18AEV

(Contd. of page 1)

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

IF ON SKIN: Wash with plenty of water.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous	· Dangerous components:	
7440-38-2	arsenic	2.5-<10%
7440-31-5	tin	2.5-<10%
	red phosphorus	2.5-<10%
7429-90-5	aluminium	2.5-<10%
7440-47-3	chromium	2.5-<10%
	molybdenum	0.1-≤2.5%
7439-92-1	lead	0.1-≤2.5%
7704-34-9	sulfur	1-≤2.5%
	(C	Contd. on page 3)

ÚS-

Printing date 10/19/2015 Reviewed on 10/10/2015

Trade name: UT18AEV

7440-02-0 nickel (Contd. of page 2)
0.1-<1%

*

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: The product is not flammable.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

ų.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- · Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up: No special measures required.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

*

7 Handling and storage

- · Handling:
- · Precautions for safe handling Not applicable.
- · Information about protection against explosions and fires: Not applicable.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

Printing date 10/19/2015 Reviewed on 10/10/2015

Trade name: UT18AEV

· Specific end use(s) No further relevant information available.

(Contd. of page 3)

8 Exposure controls/personal protection

Com	ponents with limit values that require monitoring at the workplace:
7440	-38-2 arsenic
PEL	Long-term value: 0.5* 0.01** mg/m³ as As; *organic**inorg. compds.; 29 CFR 1910.1018
REL	Ceiling limit value: 0.002 mg/m³ as As; 15min; See Pocket Guide App. A
TLV	Long-term value: 0.01 mg/m³ as As; BEI
7440	-31-5 tin
PEL	Long-term value: 2 mg/m³ metal
REL	Long-term value: 2 mg/m³
TLV	Long-term value: 2 mg/m³ metal
7723	-14-0 red phosphorus
REL	Long-term value: 0.1 mg/m³
7429	-90-5 aluminium
PEL	Long-term value: 15*; 15** mg/m³ *Total dust; ** Respirable fraction
REL	Long-term value: 10* 5** mg/m³ as Al*Total dust**Respirable/pyro powd./welding f.
7440	-47-3 chromium
PEL	Long-term value: 1* 0.5** mg/m³ *metal;**inorganic compds., as Cr
REL	Long-term value: 0.5* mg/m³ *metal+inorg.compds.as Cr;See Pocket Guide App. C
TLV	Long-term value: 0.5 mg/m³
7439	-98-7 molybdenum
PEL	Long-term value: 15* mg/m³ *Total dust
TLV	Long-term value: $10*3**mg/m^3$ as Mo; *inhalable fraction ** respirable fraction
7439	-92-1 lead
PEL	Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025
REL	Long-term value: 0.05* mg/m³
	*8-hr TWA,excl. lead arsenate;See PocketGuideApp.C

(Contd. on page 5)

Reviewed on 10/10/2015 Printing date 10/19/2015

Trade name: UT18AEV

(Contd. of page 4) TLV Long-term value: 0.05* mg/m³ *and inorganic compounds, as Pb; BEI 7440-02-0 nickel PEL Long-term value: 1 mg/m³ REL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A TLV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction

· Ingredients with biological limit values:

7440-38-2 arsenic

BEI 35 µg As/L

Medium: urine

Time: end of workweek

Parameter: Inorganic arsenic plus methylated metabolites (background)

7439-92-1 lead

BEI 30 μg/100 ml

Medium: blood Time: not critical Parameter: Lead

10 μg/100 ml Medium: blood Time: not critical

Parameter: Lead (women of child bearing potential)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. (Contd. on page 6)

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2015 Reviewed on 10/10/2015

Trade name: UT18AEV

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Solid

Color: According to product specification

Odor: CharacteristicOdour threshold: Not determined.

· pH-value: Not applicable.

· Change in condition

· Flammability (solid, gaseous):

Melting point/Melting range:Undetermined.Boiling point/Boiling range: $74 \, ^{\circ}C \, (165 \, ^{\circ}F)$

· Flash point: Not applicable.

• Ignition temperature: 300 °C (572 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

Not determined.

Explosive when mixed with oxidising substances.

· Explosion limits:

 Lower:
 0.0 Vol %

 Upper:
 0.0 Vol %

· Vapor pressure: Not applicable.

• Density at 20 °C (68 °F): 6.58812 g/cm³ (54.978 lbs/gal)

Relative density
Vapour density
Evaporation rate
Not determined.
Not applicable.
Not applicable.

· Solubility in / Miscibility with

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

(Contd. on page 7)

Printing date 10/19/2015 Reviewed on 10/10/2015

Trade name: UT18AEV

(Contd. of page 6)

	(Cond. of page of
· Solvent content: Organic solvents:	0.0 %
Solids content: · Other information	93.4 % No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

7440-38-2 arsenic

Oral LD50 763 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Res	earch on Cancer)
7440-38-2 arsenic	1
7440-47-3 chromium	3
7439-92-1 lead	21
7440-02-0 nickel	1
· NTP (National Toxicology Program)	
7440-38-2 arsenic	K
7439-92-1 lead	I.
7440-02-0 nickel	F
· OSHA-Ca (Occupational Safety & H	ealth Administration)
7440-38-2 arsenic	

(Contd. on page 8)

Printing date 10/19/2015 Reviewed on 10/10/2015

Trade name: UT18AEV

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, ADN, IMDG, IATA	not regulated
UN proper shipping name DOT, ADN, IMDG, IATA	not regulated
Transport hazard class(es)	
DOT, ADN, IMDG, IATA	
Class	not regulated
Packing group	
DOT, IMDG, IATA	not regulated
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 9)

Printing date 10/19/2015 Reviewed on 10/10/2015

Trade name: UT18AEV

(Contd. of page 8)

· UN "Model Regulation": not regulated

15 Regulatory information $\cdot \textit{Safety, health and environmental regulations/legislation specific for the substance or \textit{mixture}}$ · Sara

· Section 355 (e	xtremely hazardous substances):
7723-14-0 red	l phosphorus
· Section 313 (S	pecific toxic chemical listings):
7440-38-2 ars	renic

7723-14-0 red phosphorus 7429-90-5 aluminium 7440-47-3 chromium

7439-92-1 lead

7439-96-5 manganese 7440-02-0 nickel

7440-62-2 vanadium 7440-50-8 copper

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

7440-38-2 arsenic 7439-92-1 lead

7440-02-0 nickel

· Chemicals known to cause reproductive toxicity for females:

7439-92-1 lead

· Chemicals known to cause reproductive toxicity for males:

7439-92-1 lead

· Chemicals known to cause developmental toxicity:

7439-92-1 lead

· Carcinogenic categories

· EPA (Envi	· EPA (Environmental Protection Agency)		
7440-38-2	arsenic	A	
7723-14-0	red phosphorus	D	
7440-47-3	chromium	D	
7439-92-1	lead	B2	
7439-96-5	manganese	D	
7440-50-8	copper	D	

(Contd. on page 10)

Printing date 10/19/2015 Reviewed on 10/10/2015

Trade name: UT18AEV

	(Contd. of page 9)	
· TLV (Threshold	d Limit Value established by ACGIH)	
7440-38-2 arse	enic A1	
7429-90-5 alum	ninium A4	
7440-47-3 chro	omium A4	
7439-98-7 moly	ybdenum A3	
7439-92-1 lead	l A3	
7440-02-0 nicke	tel A5	
· NIOSH-Ca (Na	ntional Institute for Occupational Safety and Health)	
7440-38-2 arsei	7440-38-2 arsenic	
7440-02-0 nicke	:el	

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

arsenic

lead

nickel

· Hazard statements

May cause an allergic skin reaction.

May cause cancer.

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

IF ON SKIN: Wash with plenty of water.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

(Contd. on page 11)

Printing date 10/19/2015 Reviewed on 10/10/2015

Trade name: UT18AEV

(Contd. of page 10)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Date of preparation / last revision 10/19/2015 / 4
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 1A: Carcinogenicity, Hazard Category 1A

Repr. 1A: Reproductive toxicity, Hazard Category 1A

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

* * Data compared to the previous version altered.

HS