

Page 1/10

Safety Data Sheet acc. to OSHA HCS

Printing date 12/06/2018

Reviewed on 08/09/2016

1 Identification

- · Product identifier
- · Trade name: CUSTOM 465 OPTIMIZED VAR MELT
- · Application of the substance / the mixture Metal working
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Carpenter Technology Corp PO Box 14662, Reading, PA 19612 101 West Bern Street READING, PA 19601 USA
- · Information department: Health and Safety Department
- · Emergency telephone number: Call CHEMTREC +1 703-741-5970 / 1-800-424-9300 CCN 842700

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- Hazard-determining components of labeling: nickel
- · Hazard statements

May cause an allergic skin reaction.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Printing date 12/06/2018

Reviewed on 08/09/2016

Trade name: CUSTOM 465 OPTIMIZED VAR MELT

(Contd. of page 1)

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 4)



Health = 0Fire = 0

Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = 0

Fire = 0

- Other hazards
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
7440-47-3	chromium	10-25%
7440-02-0	nickel	10-25%
7440-32-6	titanium	≤2.5%
7439-98-7	molybdenum	≤2.5%

Printing date 12/06/2018

Reviewed on 08/09/2016

Trade name: CUSTOM 465 OPTIMIZED VAR MELT

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- * Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: The product is not flammable.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- · Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up: No special measures required.
- · Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

7439-89-6 iron	3.2 mg/m
7440-47-3 chromium	1.5 mg/m
7440-02-0 nickel	4.5 mg/m
7440-32-6 titanium	30 mg/m ³
7439-98-7 molybdenum	30 mg/m ³
7439-96-5 manganese	$3 mg/m^3$
7440-21-3 silicon	45 mg/m ³
7440-50-8 copper	$3 mg/m^3$
7440-03-1 niobium	30 mg/m^3

(Contd. on page 4)

Printing date 12/06/2018

Reviewed on 08/09/2016

Trade name: CUSTOM 465 OPTIMIZED VAR MELT

		(Contd. of page
<i>PAC-2:</i>		
7439-89-6	iron	35 mg/m³
7440-47-3	chromium	17 mg/m³
7440-02-0	nickel	50 mg/m³
7440-32-6	titanium	330 mg/m
7439-98-7	molybdenum	330 mg/m
7439-96-5	manganese	5 mg/m^3
7440-21-3	silicon	100 mg/m
7440-50-8	copper	33 mg/m³
7440-03-1	niobium	330 mg/m
PAC-3:		
7439-89-6	iron	150 mg/m³
7440-47-3	chromium	99 mg/m³
7440-02-0	nickel	99 mg/m³
7440-32-6	titanium	2,000 mg/m
7439-98-7	molybdenum	2,000 mg/m
7439-96-5	manganese	1,800 mg/m
7440-21-3	silicon	630 mg/m³
7440-50-8	copper	200 mg/m³
7440-03-1	niobium	2,000 mg/m

7 Handling and storage

- · Handling:
- · Precautions for safe handling Not applicable.
- · Information about protection against explosions and fires: Not applicable.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

(Contd. on page 5)

Printing date 12/06/2018

Reviewed on 08/09/2016

Trade name: CUSTOM 465 OPTIMIZED VAR MELT

(Contd. of page 4)

7440-47-3 chromium

PEL Long-term value: 1 mg/m³

REL Long-term value: 0.5* mg/m³

*metal+inorg.compds.as Cr;See Pocket Guide App. C

TLV Long-term value: 0.003* 0.5** mg/m³ inh. fraction, *as Cr(III), **metal

7440-02-0 nickel

PEL Long-term value: 1 mg/m³

REL Long-term value: 0.015 mg/m³

as Ni; See Pocket Guide App. A

TLV
Long-term value: 1.5* mg/m³
elemental, *inhalable fraction

7439-98-7 molybdenum

PEL Long-term value: 15* mg/m³

*Total dust, as Mo

TLV Long-term value: 10* 3** mg/m³

as Mo; *inhalable fraction ** respirable fraction

- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

chemical mixture.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 12/06/2018 Reviewed on 08/09/2016

Trade name: CUSTOM 465 OPTIMIZED VAR MELT

Eye protection:



(Contd. of page 5)

Information on basic physical and	chemical properties	
General Information		
Appearance:	0.11.7	
Form:	Solid	
Color: Odor:	According to product specification Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not applicable.	
	110. applicable	
Change in condition Melting point/Melting range:	Undetermined.	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not determined.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard. Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not applicable.	
Density at 20 °C (68 °F):	7.85991 g/cm³ (65.59095 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not applicable.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
Water:	Insoluble.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not applicable	
Kinematic:	Not applicable.	
Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	

Printing date 12/06/2018

Reviewed on 08/09/2016

Trade name: CUSTOM 465 OPTIMIZED VAR MELT

(Contd. of page 6)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· Carcinoge	nic categories	
· IARC (Inte	ernational Agency for Research on Cancer)	
7440-47-3	chromium	3
7440-02-0	nickel	2B
NTP (Natio	onal Toxicology Program)	
7440-02-0	nickel	R
OSHA-Ca	(Occupational Safety & Health Administration)	
None of the	e ingredients is listed.	

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

Printing date 12/06/2018

Reviewed on 08/09/2016

Trade name: CUSTOM 465 OPTIMIZED VAR MELT

(Contd. of page 7)

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADN, IMDG, IATA	not regulated	
UN proper shipping name DOT, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
DOT, IMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	s II of	
MARPOL73/78 and the IBC Code	Not applicable.	
UN "Model Regulation":	not regulated	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

/440-4/-3	
7440-02-0	nickel
	manganese
7440-50-8	copper

(Contd. on page 9)

Printing date 12/06/2018

Reviewed on 08/09/2016

Trade name: CUSTOM 465 OPTIMIZED VAR MELT

(Contd. of page 8) · TSCA (Toxic Substances Control Act): All ingredients are listed. · Proposition 65 · Chemicals known to cause cancer: 7440-02-0 nickel · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. Carcinogenic categories - EPA (Environmental Protection Agency) 7440-47-3 chromium D7439-96-5 manganese D7440-50-8 copper D· TLV (Threshold Limit Value established by ACGIH) 7440-47-3 chromium A4 7440-02-0 nickel A5 7439-98-7 molybdenum *A3* · NIOSH-Ca (National Institute for Occupational Safety and Health) 7440-02-0 nickel

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).







- Signal word Danger
- · Hazard-determining components of labeling:

nickel

Hazard statements

May cause an allergic skin reaction.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

(Contd. on page 10)

Printing date 12/06/2018

Reviewed on 08/09/2016

Trade name: CUSTOM 465 OPTIMIZED VAR MELT

(Contd. of page 9)

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Environment protection department.
- Date of preparation / last revision 12/06/2018 / 1
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

* Data compared to the previous version altered.

US-